

10-02-00
JC926 U.S. PTO
09/29/00

A
JC932 U.S. PTO
09/676645
09/29/00

Patent Application Transmittal
(only for new nonprovisional applications under 37 C.F.R. 1.53(b))
Correspondence Address:
FROMMER LAWRENCE & HAUG LLP
745 FIFTH AVENUE
NEW YORK, NEW YORK 10151
TEL: (212) 588-0800
FAX: (212) 588-0500

Date: September 29, 2000
Attorney Docket No.: 450100-02736

ASSISTANT COMMISSIONER FOR PATENTS
Box Patent Application
Washington, D.C. 20231

Sir:

With reference to the filing in the United States Patent and Trademark Office
of an application for patent in the name(s) of:

Makoto YAMADA, Satoshi TSUJII, Toshihiro ISHIZAKA

entitled:

RECORDING APPARATUS, RECORDING METHOD, AND RECORD MEDIUM

The following are enclosed:

- ☒ Specification (45 pages)
- ☒ 13 Sheet(s) of Drawings
- ☒ 16 Claim(s) (including 9 independent claim(s))
- ☐ This application contains a multiple dependent claim
- ☒ Our check for \$ 1158.00, calculated on the basis of the claims as amended by any enclosed preliminary amendment as follows:

Basic Fee, \$690.00 (\$345.00) \$ 690.00
Number of Claims in excess of 20 at \$18.00 (\$9.00) each: -0-
Number of Independent Claims in excess of 3 at \$78.00 (\$39.00) each: 6 468.00
Multiple Dependent Claim Fee at \$260.00 (\$130.00) -0-
Total Filing Fee \$1158.00
☐ Assignment Recording Fee \$40.00 -0-
- ☒ Oath or Declaration and Power of Attorney
 - ☒ New ☐ signed ☒ unsigned
 - ☐ Copy from a prior application (37 C.F.R. 1.63(d))
- ☒ Certified copy of each of the following application(s) to substantiate the claim(s) for priority made in the Declaration:

<u>Application No.</u>	<u>Filed</u>	<u>In</u>
11-279994	30 September 1999	Japan
11-356037	15 December 1999	Japan

Please charge any additional fees required for the filing of this application or credit any overpayment to Deposit Account No. 50-0320.

Respectfully submitted,

FROMMER LAWRENCE & HAUG LLP
Attorneys for Applicants

By William S. Frommer
William S. Frommer
Reg. No. 25,506

FROMMER LAWRENCE & HAUG LLP

745 FIFTH AVENUE NEW YORK, NEW YORK 10151

JC914 U.S. PTO
09/676645
09/29/00

September 29, 2000

Assistant Commissioner for Patents
Washington, D.C. 20231

Re: U.S. Patent Application
Applicants: Makoto YAMADA, Satoshi TSUJII, Toshihiro ISHIZAKA
Our Ref.: 450100-02736

Dear Sir:

Enclosed are papers constituting the above patent application which is being filed under 37 C.F.R. 1.53 without a signed Declaration. Please accord a filing date and a serial number to such application and inform the undersigned thereof so that a signed Declaration and the surcharge required by 37 C.F.R. 1.16(e) may be duly filed.

Please address all correspondence to:

William S. Frommer, Esq.
FROMMER LAWRENCE & HAUG LLP
745 Fifth Avenue
New York, New York 10151

Respectfully,



William S. Frommer
Reg. No. 25,506
Attorney for Applicants
Enclosures

WILLIAM S. FROMMER
WILLIAM F. LAWRENCE
EDGAR H. HAUG
MATTHEW K. RYAN
BARRY S. WHITE
THOMAS J. KOWALSKI
JOHN R. LANE
DENNIS M. SMID *
DANIEL C. BROWN
BARBARA Z. MORRISSEY
STEVEN M. AMUNDSON
MARILYN MATTHES BROGAN
JAMES K. STRONSKI
CHARLES J. RAUBICHECK

A. THOMAS S. SAFFORD
JEROME ROSENSTOCK
RAYMOND R. WITTEKIND, PH.D.
SUSAN J. LEHNHARDT, PH.D.
RICHARD E. PARKE
Of Counsel

GORDON KESSLER
MARK W. RUSSELL *
BRUNO POLITO
GRACE L. PAN *
JEFFREY A. HOVDEN
JOE H. SHALLENBURGER
CHRISTIAN M. SMOLIZZA
GLENN F. SAVIT
ROBERT E. COLLETTI
DEXTER T. CHANG
PETER J. WAIBEL
LINDSEY A. MÖHLE
DEENA D. LEVY
DARREN M. SIMON
YUFENG LIU, PH.D.
CINDY HUANG
JOHN G. TAYLOR

*Admitted to a Bar
other than New York

J:\SONY\02736\53BAPUNS.EXM (WSF:sa)

TEL: (212) 588-0800 FAX: (212) 588-0500 E-MAIL: FIRM@FLHLAW.COM

450100-02736



"Express Mail" mailing label number EL588272954US

Date of Deposit September 29, 2000

I hereby certify that this paper or fee, and a patent application and accompanying papers, are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and are addressed to the Assistant Commissioner for Patents, Washington, DC 20231.

Charles Jackson
(Typed or printed name of person mailing paper or fee)

Charles Jackson
(Signature of person mailing paper or fee)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants : Makoto YAMADA et al.
Filed : Herewith
For : RECORDING APPARATUS, RECORDING METHOD, AND RECORD
MEDIUM

745 Fifth Avenue
New York, New York 10151
Tel. (212) 588-0800

EXPRESS MAIL

Mailing Label Number EL588272954US
Date of Deposit September 29, 2000
I hereby certify that this paper or fee is being
deposited with the United States Postal Service
"Express Mail Post Office to Addressee" Service
under 37 CFR 1.10 on the date indicated above and
is addressed to the Assistant Commissioner for
Patents, Washington, D.C. 20231.

Charles Jackson
(Typed or printed name of person
mailing paper or fee)

Charles Jackson
(Signature of person mailing paper or fee)

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Before the issuance of the first Official Action,
please amend the above-identified application as follows:

IN THE CLAIMS:

Please amend the claims as follows:

Claim 6, line 2, delete "or 3";

Claim 7, line 2, delete "or 2".

Add new claims 15 and 16 as follows:

--15. The recording apparatus as set forth in claim 3, wherein the audio data is compression-encoded corresponding to ATRAC, and wherein the first data unit of the file structure contains one or a plurality of sound units.--

--16. The recording apparatus as set forth in claim 2, wherein the file structure further includes a data portion that describes management information, and wherein the data portion describes the number of the second data units contained in the successive record length.--

REMARKS

The claims have been amended to eliminate multiple dependencies. The filing fee has been calculated based upon these amendments to the claims.

Respectfully submitted,

FROMMER LAWRENCE & HAUG LLP
Attorneys for Applicants

By 

William S. Frommer
Reg. No. 25,506
Tel. (212) 588-0800

PATENT
450100-02736

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

TITLE: RECORDING APPARATUS, RECORDING METHOD,
AND RECORD MEDIUM

INVENTORS: Makoto YAMADA, Satoshi TSUJII,
Toshihiro ISHIZAKA

William S. Frommer
Registration No. 25,506
FROMMER LAWRENCE & HAUG LLP
745 Fifth Avenue
New York, New York 10151
Tel. (212) 588-0800

RECORDING APPARATUS, RECORDING METHOD, AND
RECORD MEDIUM

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a recording apparatus, a recording method, and a record medium having a multimedia data format such as QuickTime.

Description of the Related Art

10 In recent years, as a multi-media system software program, QuickTime is known. The QuickTime is a software program that allows data that varies on time base (this data is referred to as movie) to be handled. A movie contains a moving picture, a voice, and a text. Currently, a QuickTime file format is available as a
15 Macintosh platform of Apple. The QuickTime file format is an MPEG-1 (Moving Picture Experts Group phase 1) program stream file storage format of which a video elementary stream and an audio elementary stream are multiplexed on time base). In the storage format, the
20 entire MPEG-1 file (namely, one whole closed scene) is treated as a sample of the QuickTime file format regardless of the duration thereof. Such a large sample is treated as one large chunk.

25 In addition, audio data and video data are stored together on one track (or one medium) in the QuickTime file format. As a new medium type that represents such data portions contained in a large

sample or a large chunk, MPEG Media has been defined.

The accessibility and editing efficiency of a particular type of data contained in a large sample deteriorate. To allow a computer to reproduce and edit a QuickTime movie file, video data and audio data recorded on a record medium (for example, an optical disc) of the portable recording and reproducing apparatus with built-in camera may be converted into a QuickTime file format. In this case, the accessibility and editing efficiency of a particular type of data should be further improved. This problem applies to an audio data recording and reproducing apparatus as well as such a video data recording and reproducing apparatus.

OBJECTS AND SUMMARY OF THE INVENTION

Therefore, an object of the present invention is to provide a recording apparatus, a recording method, and a record medium that allow the accessibility and editing efficiency to be improved in the case that data having a file structure corresponding to a multimedia data format such as QuickTime is recorded to a record medium.

A first aspect of the present invention is a recording apparatus for recording video data to a rewritable optical disc, comprising an encoding means for encoding video data corresponding to a compression-

encoding process, a converting means for converting the data structure of the encoded video data received from the encoding means into a file structure that allows a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware, and a recording means for recording data having the file structure to an optical disc, wherein the file structure has a first data unit and a second data unit, the second data unit being a set of the first data units, and wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

A second aspect of the present invention is a recording apparatus for recording audio data to a rewritable optical disc, comprising a converting means for converting the data structure of audio data or encoded audio data into a file structure that allows a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware, and a recording means for recording data having the file structure to an optical disc, wherein the file structure has a first data unit and a second data unit, the second data unit being a set of the first data units, and wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

A third aspect of the present invention is a

recording apparatus for recording video data and audio data to a rewritable optical disc, comprising a video encoding means for encoding video data corresponding to a compression-encoding process in a combination of an inter-frame predictive encoding process and a motion compensating process that allow a plurality of frames are structured as a group, an audio output means for outputting audio data that has been compression-encoded or non-compressed, a multiplexing means for converting the data structure of the encoded video data received from the encoding means and the data structure of the audio data received from the audio output means into respective file structures that allow a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware and multiplexing the encoded video data and the audio data, and a recording means for recording the multiplexed data to an optical disc, wherein each of the file structures has a first data unit and a second data unit, the second data unit being a set of the first data units, and wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

A fourth aspect of the present invention is a recording method for recording video data to a rewritable optical disc, comprising the steps of encoding video data corresponding to a compression-

encoding process, converting the data structure of the encoded video data received at the encoding step into a file structure that allows a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware, and recording data having the file structure to an optical disc, wherein the file structure has a first data unit and a second data unit, the second data unit being a set of the first data units, and wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

A fifth aspect of the present invention is a recording method for recording audio data to a rewritable optical disc, comprising the steps of converting the data structure of audio data or encoded audio data into a file structure that allows a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware, and recording data having the file structure to an optical disc, wherein the file structure has a first data unit and a second data unit, the second data unit being a set of the first data units, and wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

A sixth aspect of the present invention is a recording method for recording video data and audio

data to a rewritable optical disc, comprising the steps
of encoding video data corresponding to a compression-
encoding process in a combination of an inter-frame
predictive encoding process and a motion compensating
process that allow a plurality of frames are structured
as a group, outputting audio data that has been
compression-encoded or non-compressed, converting the
data structure of the encoded video data received at
the encoding step and the data structure of the audio
data received at the outputting step into respective
file structures that allow a moving picture to be
synchronously reproduced by computer software without
need to use specially dedicated hardware and
multiplexing the encoded video data and the audio data,
and recording the multiplexed data to an optical disc,
wherein each of the file structures has a first data
unit and a second data unit, the second data unit being
a set of the first data units, and wherein a plurality
of the second data units is matched with a successive
record length of which data is written to the optical
disc.

A seventh aspect of the present invention is
a record medium on which a program for recording video
data to a record medium has been recorded, the program
causing a computer to perform the steps of encoding
video data corresponding to a compression-encoding
process, converting the data structure of the encoded

video data received at the encoding step into a file structure that allows a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware, and recording data having the file structure to an optical disc, wherein the file structure has a first data unit and a second data unit, the second data unit being a set of the first data units, and wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

An eighth aspect of the present invention is a record medium on which a program for recording audio data to a record medium has been recorded, the program causing a computer to perform the steps of converting the data structure of audio data or encoded audio data into a file structure that allows a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware, and recording data having the file structure to an optical disc, wherein the file structure has a first data unit and a second data unit, the second data unit being a set of the first data units, and wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

A ninth aspect of the present invention is a record medium on which a program for recording video

data and audio data to a record medium has been
recorded, the program causing a computer to perform the
steps of encoding video data corresponding to a
compression-encoding process in a combination of an
5 inter-frame predictive encoding process and a motion
compensating process that allow a plurality of frames
are structured as a group, outputting audio data that
has been compression-encoded or non-compressed,
converting the data structure of the encoded video data
10 received at the encoding step and the data structure of
the audio data received at the outputting step into
respective file structures that allow a moving picture
to be synchronously reproduced by computer software
without need to use specially dedicated hardware and
15 multiplexing the encoded video data and the audio data,
and recording the multiplexed data to an optical disc,
wherein each of the file structures has a first data
unit and a second data unit, the second data unit being
a set of the first data units, and wherein a plurality
20 of the second data units is matched with a successive
record length of which data is written to the optical
disc.

When data having a file structure is recorded
to an optical disc, since the successive record length
25 is matched with a second data unit (for example, a
chunk of QuickTime), the accessibility and editing
efficiency can be improved. In addition, since a

plurality of sets of encoded video data and audio data (compressed or non-compressed) are matched with the successive record length, the accessibility and editing efficiency can be improved.

5 The following US patents are prior patent of the present invention.

- (1) US Patent No. 4,945,475
- (2) US Patent No. 5,253,053
- (3) US Patent No. 5,652,879

10 In addition, the applicant of the present invention has filed the following Japanese patent applications.

- (1) Japanese Patent Application No. 11-264630 filed on September 17, 1999
- 15 (2) Japanese Patent Application No. 11-264631 filed on September 17, 1999
- (3) Japanese Patent Application No. 11-279993 filed on September 30, 1999

20 These and other objects, features and advantages of the present invention will become more apparent in light of the following detailed description of a best mode embodiment thereof, as illustrated in the accompanying drawings.

25 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the structure of an embodiment of the present invention;

Fig. 2 is a schematic diagram showing an example of a QuickTime file format according to the present invention;

Fig. 3 is a schematic diagram showing the detailed data structure of a movie resource of QuickTime;

Fig. 4 is a schematic diagram showing the detailed data structure of the movie resource of QuickTime;

Figs. 5A and 5B are schematic diagrams for explaining the relation between GOPs of the MPEG video and a QuickTime file format according to the embodiment of the present invention;

Figs. 6A and 6B are schematic diagrams for explaining an example of the relation between compression-encoded audio data and a QuickTime file format according to the embodiment of the present invention;

Figs. 7A and 7B are schematic diagrams for explaining another example of the relation between compression-encoded audio data and a QuickTime file format according to the embodiment of the present invention;

Figs. 8A, 8B, 8C, and 8D are schematic diagrams for explaining the relation between GOPs of MPEG video data and a QuickTime file format according to the embodiment of the present invention;

Figs. 9A, 9B, 9C, and 9D are schematic diagrams for explaining another example of the relation between compression-encoded audio data and a QuickTime file format according to the embodiment of the present invention;

Fig. 10 is a schematic diagram for explaining an example of a recording method for an optical disc according to the embodiment of the present invention;

Fig. 11 is a schematic diagram showing a general data structure of a QuickTime movie file composed of two tracks of a video track and an audio track;

Fig. 12 is a schematic diagram showing the detailed data structure of a sample description according to the embodiment of the present invention; and

Figs. 13A, 13B, 13C, 13D, 13E, 13F, and 13G are schematic diagrams for explaining several examples of a chunk flag and chunk numbers according to the embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, an embodiment of the invention will now be described with reference to the drawings. Fig. 1 shows an example of the structure of a digital recording and reproducing apparatus according to the embodiment of the present invention. In Fig. 1, 1

denotes digital encoder. A video input is supplied to video encoder 1. The video encoder 1 compression-encodes the video signal. Thus, 2 denotes audio encoder. As audio inputs of audio encoder 2, an audio signal is compression-encoded. For example, MPEG is used for the compression-encoding process toward video signals and audio signals. The outputs of video encoder 1 and audio encoder 2 are referred as the element streams.

When MPEG is used, the video encoder 1 is composed of a motion predicting portion, a picture sequence rearranging portion, a subtracting portion, a DCT portion, a quantizing portion, a variable length code encoding portion, and a buffer memory. The motion predicting portion detects a moving vector. The subtracting portion forms a predictive error between an input picture signal and a locally decoded picture signal. The DCT portion transforms an output signal of the subtracting portion corresponding to the DCT method. The quantizing portion quantizes an output signal of the DCT portion. The variable length encoding portion encodes an output signal of the quantizing portion into a signal having a variable length. The buffer memory outputs the encoded data at a constant data rate. The picture sequence rearranging portion rearranges the sequence of pictures corresponding to the encoding process. In other words,

the picture sequence rearranging portion rearranges the sequence of pictures so that after I and P pictures are encoded, a B picture is encoded. The local decoding portion is composed of an inverse quantizing portion,
5 an inverse DCT portion, an adding portion, a frame memory, and a motion compensating portion. The motion compensating portion performs all of a forward predicting operation, a reverse predicting operation, and a bidirectional predicting operation. When the intra encoding process is performed, the subtracting
10 portion directly passes data, not performs the subtracting process. The audio encoder 2 comprises a sub-band encoding portion and an adaptively quantized bit allocating portion.

15 As an example, in the case of a portable disc recording and reproducing apparatus with a built-in camera, a picture photographed by the camera is input as video data. In addition, a voice collected by a microphone is input as audio data. The video encoder 1
20 and the audio encoder 2 convert analog signals into digital signals. According to the embodiment of the present invention, a rewritable optical disc is used as a record medium. Examples of such an optical disc are a magneto-optical disc and a phase-change type disc.
25 According to the embodiment of the present invention, a magneto-optical disc having a relatively small diameter is used.

Output signals of the video encoder 1 and the audio encoder 2 are supplied to a file generator 5. The file generator 5 converts output signals of the video encoder 1 and the audio encoder 2 into a video elementary stream and an audio elementary stream so that they can be handled corresponding to a computer software program for synchronously reproducing a moving picture and a sound without need to use a dedicated hardware portion. According to the embodiment of the present invention, for example, as such a software program, QuickTime is used. A sequence of data (video data, audio data, and text data) that varies on time base and that is process by QuickTime is referred to as QuickTime movie. The file generator 5 multiplexes encoded video data and encoded audio data. To generate a QuickTime movie file, a system controlling microcomputer 9 controls the file generator 5.

QuickTime movie files generated by the file generator 5 are successively written to a memory 7 through a memory controller 8. When the system controlling microcomputer 9 issues a data write request for a disc to the memory controller 8, the memory controller 8 reads a QuickTime movie file from the memory 7. In this example, the transfer rate of the encoding process for a QuickTime movie file is lower than that for data written to the disc. For example, the former is half of the latter. Thus, although

QuickTime movie files are successively written to the memory 7, they are intermittently read from the memory 7 under the control of the system controlling microcomputer 9 in such a manner that the memory 7 is prevented from overflowing or underflowing.

A QuickTime movie file that is read from the memory 7 through the memory controller 8 is supplied to an error correction encoder/decoder 11. The error correction encoder/decoder 11 temporarily writes a QuickTime movie file to a memory 10. The error correction encoder/decoder 11 performs an interleaving process and an error correction code encoding process so as to generate redundant data. The error correction encoder/decoder 11 reads the QuickTime movie file with redundant data from the memory 10.

Output data of the error correction encoder/decoder 11 is supplied to a data modulator/demodulator 13. When digital data is recorded on the disc, the data modulator/demodulator 13 modulates the data in such a manner that a clock signal can be easily extracted so that data can be recorded on a disc free from a problem such as an inter-code interference. For example, RLL (1, 7) can be used.

An output signal of the data modulator/demodulator 13 is supplied to a magnetic field modulating driver 14. In addition, a signal for driving an optical pickup 23 is output to the magnetic

field modulating driver 14. The magnetic field modulating driver 14 drives a magnetic field head 22 corresponding to the input signal so as to apply a magnetic field to an optical disc 20. The optical pickup 23 radiates a recording laser beam to the optical disc 20. In such a manner, data is recorded on the optical disc 20. The optical disc 20 is rotated at CLV (Constant Linear Velocity), CAV (Constant Angular Velocity), or ZCAV (Zone CLV of which the disc surface area is divided into for example three areas in each of which the optical disc 20 is rotated at CAV in such a manner that the velocity of the innermost area is the highest and the velocity of the outermost area is the lowest).

Since data that is intermittently read from the memory controller 8 is recorded to the optical disc 20, data is not successively recorded. In other words, after a predetermined amount of data is recorded, the recording operation is stopped until the next record request is received.

When the system controlling microcomputer 9 issues a request to a drive controlling microcomputer 12, it issues a request to a servo circuit 15 so as to control the entire disc drive. Thus, the disc drive performs a recording operation. The servo circuit 15 performs a disc radial moving servo operation, a tracking servo operation, and a focus servo operation

for the optical pickup 23. In addition, the servo circuit 15 performs a spindle servo operation for a motor 21. In association with the system controlling microcomputer 9, a user operation input portion (not shown) is disposed.

Next, the structure and operation of the reproducing portion will be described. When data is reproduced, a reproducing laser beam is radiated to the optical disc 20. A detector of the optical pickup 23 converts the reflected light of the optical disc 20 into a reproduction signal. A tracking error and a focus error are detected from an output signal of the detector of the optical pickup 23. The servo circuit 15 controls the optical pickup 23 so that the optical pickup 23 is placed and focused on a desired track. In addition, the servo circuit 15 controls the radial movement of the optical pickup 23 so that it reproduces data on a desired track of the optical disc 20.

As with the recording operation, when data is reproduced, the transfer rate of data reproduced from the optical disc 20 is higher than that of a QuickTime movie file. For example, the transfer rate of data reproduced from the optical disc 20 is twice as large as the transfer rate of a QuickTime movie file.

Likewise, data is not successively reproduced from the optical disc 20. In other words, an intermittent reproducing operation is performed in such a manner

that after a predetermined amount of data is reproduced, the reproducing operation is stopped until the next reproducing request is received. As with the recording operation, in the reproducing operation, when
5 the system controlling microcomputer 9 issues a request to the drive controlling microcomputer 12, it issues a request to the servo circuit 15 so as to control the entire disc drive.

The reproduction signal that is output from the optical pickup 23 is input to the data modulator/demodulator 13. The data modulator/demodulator 13 demodulates the reproduction signal. The demodulated data is supplied to the error correction encoder/decoder 11. The error correction
10 encoder/decoder 11 temporarily writes the reproduction data to the memory 10. The error correction encoder/decoder 11 performs a deinterleaving process and an error correcting process for the reproduction data. The error-corrected QuickTime movie file is
15 written to the memory 7 through the memory controller 8.
20

A QuickTime movie file written to the memory 7 is output to a file decoder 6 in synchronization with a demultiplexing timing corresponding to a request
25 issued by the system controlling microcomputer 9. The system controlling microcomputer 9 supervises the amount of data that is reproduced from the optical disc

20 and written to the memory 7 and the amount of data
that is read from the memory 7 and output to the file
decoder 6 so as to successively reproduce the video
signal and the audio signal. In addition, the system
controlling microcomputer 9 controls the memory
controller 8 and the drive controlling microcomputer 12
so as to read data from the optical disc 20 in such a
manner that the memory 7 does not overflow or
underflow.

The file decoder 6 decodes a QuickTime movie
file into a video elementary stream and an audio
elementary stream under the control of the system
controlling microcomputer 9. The video elementary
stream is supplied to a video decoder 3. The audio
elementary stream is supplied to an audio decoder 4.
The video elementary stream and the audio elementary
stream are synchronously output from the file decoder
6.

The video decoder 3 and the audio decoder 4
compression-decode the video elementary stream and the
audio elementary stream and generate a video output
signal and an audio output signal, respectively. In
this example, the video signal and the audio signal
have been encoded corresponding to MPEG. A video
output signal is output to a display (liquid crystal
display or the like) through a display driver and
displayed as a picture. Likewise, an audio output

signal is output to a speaker through an audio amplifier and reproduced as a sound (these structural portions are not shown).

5 The video decoder 3 is composed of a buffer memory, a variable length code decoding portion, an inverse DCT portion, an inverse quantizing portion, an adding portion, and a local decoding portion. The adding portion adds an output signal of the inverse quantizing portion and a local decoded output signal. The local decoding portion is composed of a picture sequence rearranging portion, a frame memory, and a motion compensating portion. When an intra encoding process is performed, the adding portion directly passes data, not performs the adding process. Decoded data is output from the adding portion to the picture sequence rearranging portion. The picture sequence rearranging portion rearranges the decoded pictures in the original order.

20 As was described above, since the optical disc 20 on which data is recorded is attachable and detachable, the data recorded on the optical disc 20 can be reproduced by another apparatus. For example, a personal computer that operates with QuickTime application software may read data recorded on the optical disc 20 and reproduce video data and audio data therefrom. It should be noted that the present invention can be applied to an apparatus that handles

only video data or only audio data.

Next, the embodiment of the present invention will be described in more detail. First of all, with reference to Fig. 2, QuickTime will be described in brief. QuickTime is an OS expansion function for reproducing a moving picture without need to use dedicated hardware. There are various data formats for QuickTime. In other words, audio data, video data, MDI, and so forth of up to 32 tracks can be synchronously output.

A QuickTime movie file is roughly divided into two portions that are a movie resource portion and a movie data portion. The movie resource portion contains time data that represents the duration of the QuickTime movie file and information necessary for referencing real data. On the other hand, the movie data portion contains real video data and real audio data.

One QuickTime movie file can contain different types of medium data such as a sound, a video, and a text as independent tracks that are a sound track, a video track, and a text track, respectively. These independent tracks are strictly controlled on time base. Each track has a medium for referencing the compression method of the real data and the display time period thereof. The medium contains the minimum sample size of the real data in the movie

data portion, the position of a chunk that is a block of a plurality of samples, and the display duration of each sample.

Fig. 2 shows an example of a QuickTime file that handles audio data and video data. The largest structural portions of the QuickTime file are a movie resource portion and a movie data portion. The movie resource portion contains the duration necessary for reproducing the file and data necessary for referencing the real data. The movie data portion contains real data of video data, audio data, and so forth.

Next, the structure of the movie resource portion will be described in detail. A QuickTime movie file has a hierarchical structure of a movie resource portion 50, a track portion 51, a media portion 52, a median formation portion 53, and a sample table portion 54. The track portion 51 describes information about each part of the movie data. The media portion 52 describes information of each part of data. The movie resource portion 50 is used for one video track.

Likewise, one QuickTime movie file contains a resource portion 55 for an audio track. The structure of the resource portion 55 is the same as the structure of the movie resource portion 50.

The movie resource portion 50 contains a movie header 41 that describes general information about the file. The track portion 51 contains a track

header 42 that describes general information about the track. The media portion 52 contains a media header 43 and a media handler 44. The media header 43 describes general information about the media. The media handler 44 describes information for handling the media data. The media information portion 53 contains a media header 45, a data handler 46, and data information portion 47. The media header 45 describes information about the picture media. The data handler 46 describes information for handling the picture data. The data information portion 47 describes information about the data. The sample table portion 54 contains a sample description 57, a time-to-sample, a sample size 48, a sample-to-chunk, a chunk offset 49, a sync sample, and so forth. The sample description 57 describes each sample. The time-to-sample describes the relation between samples and time base. The sample size 48 describes the size of the sample. The sample-to-chunk describes the relation between samples and chunks. The chunk offset 49 describes the start byte position of the chunk in the movie file. The sync sample describes information about synchronization.

On the other hand, the movie data portion 56 contains audio data encoded corresponding to for example MPEG audio layer 2 and vide data encoded in the compression-encoding method corresponding to for example MPEG (Moving Picture Expert Group) method in

the unit of chunks each of which is composed of a predetermined number of samples. However, it should be noted that the present invention is not limited to such an encoding method. In addition, the moving data portion 56 may contain linear data that has not been compression-encoded.

Each track of the movie resource portion is correlated with data contained in the movie data portion. In other words, in the example shown in Fig. 2, since audio data and video data are handled, the movie resource portion contains a video track and an audio track. The movie data portion contains real audio data and real video data. When other types of data are handled, the movie resource portion contains their tracks and the movie data portion contains real data thereof. For example, when a text and MIDI are handled, the movie resource portion contains tracks of the text and the MIDI and the movie data portion contains real data thereof.

Figs. 3 and 4 show a first portion and a second portion of the detailed data structure of the movie resource portion of the QuickTime movie file, respectively. As was described with reference to Fig. 2, the movie resource portion 50 has a hierarchical structure of the track portion 51, the media portion 52, media information portion 53, and the sample table portion 54. The track portion 51 describes information

about individual data parts of the movie data. The media portion 52 describes information about individual data parts. As was described above, the movie resource portion is used for one video track. Likewise, the audio resource portion 55 (not shown) is used for one audio track. The structure of the movie resource portion 50 is the same as the structure of the audio resource portion 55.

Next, a method for converting compressed video data (video elementary stream) and compressed audio data (audio elementary stream) into a QuickTime file format in the case that MPEG2 is used as a decoding method for data that has been compression-encoded will be described. First of all, MPEG will be described. MPEG has a hierarchical structure of six layers that are a sequence layer, a GOP layer, a picture layer, a slice layer, a macro block layer, and a block layer in the order of the highest hierarchical level. A header is placed at the beginning of each of the six layers. For example, a sequence header is a header placed at the beginning of the sequence layer. The sequence header contains a sequence start code, a horizontal screen size, a vertical screen size, an aspect ratio, a picture rate, a bit rate, a VBV buffer size, a restriction parameter bit, a load flag of two quantized matrixes, and a content.

According to MPEG, there are three picture

types I, P, and B. In an I picture (Intra-coded picture), when a picture signal is encoded, information of only one picture is used. Thus, when an encoded picture signal is decoded, information of only the I picture is used. In a P picture (Predictive-coded picture), as a predictive picture (a reference picture for obtaining a difference with the current P picture), an I picture or another P picture that has been decoded is temporally followed by the current P picture. The difference between the current P picture and a motion-compensated predictive picture is encoded for each macro block. Alternatively, the current P picture is encoded for each macro block without obtaining the difference of such pictures. One of those methods is selected whichever higher efficiency is obtained. In a B picture (Bidirectionally predictive-coded picture), as predictive pictures (reference pictures for obtaining a difference with the current B picture), three types of reference pictures are used. The first type reference picture is an I picture or a P picture that has been decoded and that is temporally followed by the current B picture. The second type reference picture is an I picture or a P picture that has been decoded and that is temporally preceded by the current B picture. The third type reference picture is an interpolated picture of the first type reference picture and the second type reference picture. The

difference between the current B picture and each of the three type reference pictures that have been motion-compensated is encoded for each macro block. Alternatively, the current B picture is encoded for each macro block without obtaining such a difference. One of those methods is selected whichever higher efficiency is obtained.

Thus, there are a frame intra-coded macro block, a forward inter-frame predictive macro frame (a future macro block is predicted with a past macro block), a backward inter-frame predictive macro block (a past macro block is predicted with a future macro block), and a bidirectional macro block (a current macro block is predicted with both a future macro block and a past macro block). All macro blocks in an I picture are intra-frame coded macro blocks. A P picture contains intra-frame coded macro blocks and forward inter-frame predictive macro blocks. A B picture contains the above-described four types of macro blocks.

In MPEG, a GOP (Group Of Pictures) structure that is a group of pictures is defined so that data can be random-accessed. In MPEG, a GOP is defined as follows. The first picture of one GOP is an I picture. The last picture of one GOP is an I picture or a P picture. A GOP that is predicted with the last I or P picture of the preceding GOP is permitted. A GOP that

can be decoded without a picture of the preceding GOP is referred to as closed GOP. According to the embodiment, as a structure of a closed GOP, each GOP can be edited.

5 In MPEG audio (compressing method), three modes of layer 1, layer 2, and layer 3 have been defined. In layer 1, for example 32 sub-band encoding operation and adaptive bit allocating operation are performed. One audio decoding unit is composed of 384 samples. One audio decoding unit is one audio frame of an audio bit stream. The audio decoding unit is the minimum unit of which encoded data is decoded to audio data. Likewise, the video decoding unit corresponding to one video frame has been defined. In NTSC system, one video frame is equivalent to 1/30 seconds. Normally, the bit rate of stereo audio in layer 1 is 256 kbps. In layer 2, a 32 sub-band encoding operation and an adaptive bit allocating operation are performed. One audio decoding unit is composed of 1152 samples. 10
15
20 Normally, the bit rate of stereo audio in layer 2 is 192 kbps.

 The file generator 5 converts video data and audio data that have been compressed corresponding to MPEG into a file structure corresponding to the above-
25 described QuickTime file format. Figs. 3A and 3B show the relation among video frames, GOPs, and units of samples and chunks of the QuickTime file format. As

was described above, one sample is the minimum unit of movie data. One chunk is a unit of which a plurality of samples are collected as a block.

As shown in Fig. 5A, for example 15 video frames of an original video signal are compression-encoded corresponding to MPEG2 and thereby one GOP is generated. 15 video frames are equivalent to 0.5 seconds. Each GOP is preferably structured as a closed GOP. A sequence header (SH) is placed at the beginning of each GOP. The sequence header and one GOP compose one video decoding unit. Since a sequence header is placed to each GOP, each sample can be directly edited and decoded with QuickTime. The video encoder 1 shown in Fig. 1 outputs an MPEG video elementary stream shown in Fig. 5A.

As shown in Fig. 5B, one video decoding unit is treated as one sample of the QuickTime file format. Two chronologically successive samples (for example, sample #0 and sample #1) are treated as one video chunk (for example, chunk #0). The duration of one chunk is 3 seconds. Alternatively, six GOPs may be treated as one sample, whereas one video chunk may be treated as one sample. In this case, the duration of one video chunk is 3 seconds.

Fig. 6 A and 6B show the relation among audio frames encoded corresponding to MPEG audio layer 2 (256 kbps in two-channel stereo), an audio decoding unit,

GOPs, and units of samples and chunks in the QuickTime file format. In layer 2, 1152 audio samples/channel are treated as one audio frame. As shown in Fig. 6A, in stereo, audio data of 1152 samples x 2 channels is encoded in layer 2 and treated as one audio decoding unit. One audio decoding unit contains data of 384 bytes x 2 channels that have been compression-encoded. The audio decoding unit contains a header and information necessary for decoding the encoded data (allocation, scale factor, and so forth).

As shown in Fig. 6B, one audio decoding unit is treated as one sample of the QuickTime file format. Thus, each audio sample can be decoded with QuickTime. 41 chronological successive samples (for example, sample #0 to sample #40) are treated as one audio chunk (for example, chunk #0). 42 chronological successive samples (for example, sample #41 to sample #82) are treated as one audio chunk (for example, chunk #1). 42 chronological successive samples (for example, sample #83 to sample #124) are treated as one audio chunk (for example, chunk #2). When the audio sampling frequency is 48 kHz, the duration of one audio chunk is around 1 second. Thus, the duration of three successive audio chunks is three seconds.

In Figs. 5A, 5B, 6A, and 6B, the structure of video data and the structure of audio data are separately shown. The file generator 5 multiplexes

video data and audio data as one data stream (this process is also referred to as interleaving) and thereby generates a QuickTime movie file. In the QuickTime movie file, video chunks and audio chunks are alternatively placed in the data. In this case, video chunks and audio chunks are placed in such a manner that a video chunk synchronizes with an audio chunk corresponding thereto (for example, the video chunk #0 shown in Fig. 5B and the audio chunk #0 shown in Fig. 6B). As was described above, the duration of video data of one video chunk is equal to the duration of audio data of one audio chunk (for example, one second). The duration of one audio chunk is not exactly one second. However, the duration of three video chunks is equal to the duration of three audio chunks (three seconds).

As another example of the audio compression-encoding method, ATRAC (Adaptive Transform Acoustic Coding) used for Mini Disc may be used. In ATRAC, audio data of 16 bits sampled at 44.1 kHz is processed. The minimum data unit processed in ATRAC is one sound unit. In stereo, one sound unit is composed of 512 samples x 16 bits x 2 channels.

When ATRAC is used as an audio compression-encoding method, as shown in Fig. 7A, one sound unit is compressed to an audio decoding unit of 212 bytes x 2 channels. As shown in Fig. 7B, one audio decoding unit

is treated as one sample in the QuickTime file format.
64 samples are treated as one chunk in the QuickTime
file format.

In addition, MPEG audio layer 3, ATRAC 3
5 which is an increased compression rate and or the like
can be used as an audio compression-encoding method.
According to the present invention, the audio data may
be recorded on a non-compression basis. The non-
compression method is referred to as linear PCM.
10 Likewise, in linear PCM, 512 audio samples are treated
as one audio decoding unit. One audio decoding unit is
treated as one sample in the QuickTime file format.

Fig. 8 shows a QuickTime file format for
video data in the case that video data and audio data
are multiplexed. As shown in Fig. 8A, the period of a
15 video frame is t_0 seconds and the number of frames of
one GOP is f_0 . When original video data is encoded
corresponding to MPEG2, an MPEG video elementary stream
shown in Fig. 8B is formed. As was described above, a
20 sequence header (SH) is placed to each GOP.

As shown in Fig. 8C, one GOP with a sequence
header is treated as one sample in the QuickTime file
format. The length of one sample is referred to as
sample size. With a plurality of samples (for example,
25 six samples), one chunk is composed in the QuickTime
file format. As shown in Fig. 8D, video chunks and
audio chunks are alternately placed on time base and

thereby multiplexed. As a result, a QuickTime movie file is formed. The beginning of each video chunk of the QuickTime movie file is referred to as video chunk offset. The video chunk offset is represented by the number of bytes from the beginning of the file to the beginning of the video chunk.

Fig. 9 shows a QuickTime file format of audio data in the case that video data and audio data are multiplexed. As shown in Fig. 9A, an original audio signal is digitized. One audio frame contains f_0 audio samples \times n channels. When the original audio data is compression-encoded corresponding to MPEG audio, an MPEG audio elementary stream shown in Fig. 9B is formed.

As shown in Fig. 9C, for example one audio decoding unit is treated as one sample of the QuickTime file format. The size of one sample is referred to as sample size. A plurality of samples (for example, 125 samples) composes one chunk of the QuickTime file format. As shown in Fig. 9D, video chunks and audio chunks are alternately placed and thereby multiplexed. As a result, a QuickTime movie file is formed. The beginning of each audio chunk of a QuickTime movie file is referred to as audio chunk offset. The audio chunk offset is represented by the number of bytes from the beginning of the file to the beginning of the audio chunk. The duration of each video chunk is the same as

the duration of each audio chunk. For example, the duration is 1 or 3 seconds.

The sample size of a video sample, the sample size of an audio sample, the offset value of a video chunk, and the offset value of an audio chunk are contained in the resource of a QuickTime movie file. With the resource, each sample of each chunk can be designated and edited (in the encoding unit).

Next, as mentioned above, a recording method for recording a QuickTime movie file of which video chunks and audio chunks have been multiplexed (interleaved) to the optical disc 20 will be described. As described above, one QuickTime file format is roughly divided into two major portions that are a movie resource portion and a movie data portion. When a QuickTime movie file is recorded to the optical disc 20, as shown in Fig. 8, the movie resource is matched with the successive record length. In addition, each chunk (video chunk or audio chunk) of the movie data (real data) is matched with the successive record length of the disc. The successive record length means the length of which data can be written to successive addresses without a jumping operation of the optical pickup 23.

When video chunks and audio chunks are multiplexed, a plurality of sets of video chunks and audio chunks are matched with the successive record

length in such a manner that each video chunk adjacents
to each audio chunk corresponding thereto. For
example, as shown in Fig. 10, data for three seconds of
which three sets of video chunk #i for one second as
5 shown in Fig. 5B and audio chunk #i for one second as
shown in Fig. 6B are matched with the successive record
length on the optical disc. For example, data for
three seconds of an audio chunk #1, a video chunk #1,
...., an audio chunk #3, and a video chunk #3 are
10 recorded corresponding to one successive record length.

As shown in Fig. 10, the position of the
successive record length is physically not continuous.
Thus, after the movie resource is reproduced, when the
first audio chunk and video chunk are reproduced
15 (namely, data of two successive record lengths is
reproduced), a track jump takes place. However, as was
described above, since the data transfer rate of
write/read operation is higher (for example, two times
higher) than the data transfer rate of a QuickTime
20 movie file, even if data is intermittently read,
successive QuickTime movie files can be reproduced.

Thus, the transfer rate of a QuickTime movie
file, the read rate of data from the optical disc, the
duration of the successive record length, and the seek
25 time of the disc drive (the seek time is the duration
necessary for a track jump from one track to another
track) mutually relate. Thus, the duration of video

data and audio data recorded in the successive record length can be selected in various manners from other than 3 seconds. It is preferred that in the duration for video frames of video data recorded in the successive record length, an integer number of audio samples are placed.

According to the above-described embodiment, only video data or audio data can be recorded to an optical disc. In addition, video data and audio data can be multiplexed and recorded to an optical disc. Moreover, as a successive record length, one or a plurality of chunks can be contained. Thus, according to the embodiment, information that represents in what units audio chunks and video chunks are contained as a successive record length on the optical disc is placed in the movie resource portion (management information portion) of the QuickTime movie file. In other words, with reference to information of the management data portion of the file, data that is successively recorded on the audio track and video track can be obtained. Such information is for example information that represents the relation of tracks on which data is successively recorded and information that represents the number of chunks (or sets) contained in the successive record length.

In reality, such information is described in the sample description 57 (see Figs. 2 and 4) of the

movie resource portion of the QuickTime movie file.

Fig. 11 shows the general structure of the QuickTime movie file composed of two tracks of a video track and an audio track. The sample description 57 may contain
5 CODEC (compression-decompression method) and its attributes as information necessary for interpreting sample data.

Fig. 12 shows the structure of the sample description 57 in detail. According to the embodiment of the present invention, the sample description 57 contains seven fields defined as shown in Fig. 12 in addition to the information storing area. The field "Data format" contains information for identifying a format type such as a compression method for audio data and video data. In this example, when video data corresponding to MPEG2 and audio data corresponding to MPEG audio player 2 are recorded, the field "Data
10 format" contains a character string DMPEG as an example of the format type.

20 As with the basic structure unit of the movie resource of the QuickTime movie file, the extended seven fields are defined as a set of "size" that represents the extended portion, "type" that represents the extended contents, and "data" that represents the
25 extended data in succession.

In reality, in the example, the field "Extension size" of four bytes contains the size of all

the extended seven fields (the number of bytes) so as to represent the extended portion. The next field "Extension type" of four bytes contains a character string - for example "stde" - as the type name that represents the extended contents. In other words, the type name (stde) represents information about tracks on which chunks are successively recorded on the disc as extensively defined data. As the information, five fields (Flags, Track ID, Data reference index, Recorded data size, and Repeat number) are defined as follows.

The field "Flags" of one byte contains an information flag about an interpreting method of data placed in the fields "Track ID", "Data reference index", "Recorded data size", and "Repeat number". The field "Track ID" of four bytes, the field "Data reference index" of two bytes, the field "Recorded data size" of two bytes, and the field "Repeat number" of one byte complexly contain information that represents in what units chunks of an audio track and a video track have been interleaved and successively recorded.

The field "Flags" represents whether chunks of different tracks have been interleaved and successively written on the disc (when the value of the field "Flags" is 4) or not (when the value of the field "Flags" is 1).

The field "Track ID" represents an identification value of an index of a track. The

identification value is contained in the track header
42 shown in Figs. 2 and 3. The value of the field
"Track ID" is unique in one movie file. The field
"Track ID" defines a track on which chunks are
5 successively written.

The field "Data reference index" represents
an identification value assigned to each sample
description table that contains detailed information of
a sample in the sample description 57 (see Fig. 11) of
the track. Normally, one sample description contains
one sample description table. However, after a movie
file is edited, one sample description may contain a
plurality of sample description tables. The value of
the field "Data reference index" is unique on one
10 track. The field "Data reference table" defines a
chunk that is successively written and composed of a
sample containing sample information described in a
sample description table.
15

The field "Recorded data size" represents the
20 minimum number of chunks that are successively recorded
on the disc as chunks on one track designated by the
field "Track ID" and the field "Data reference index".

The field "Repeat number" represents the
number of times of which a set of chunks successively
25 recorded on a track designated by the fields "Track
ID", "Data reference index", and "Recorded data size"
is repeated.

In a combination of the five data fields, information of what chunks of what track have been successively recorded as a set on a disc in what order and in what unit is represented.

5 Next, examples of combinations of the five data fields will be described. For simplicity, a movie file having one audio track and one video track and a movie file having only one audio track are assumed.

10 Fig. 13A shows a first example. In the first example, there are one audio track (Track ID = 1) and one video track (Track ID = 2). Audio chunks (Data reference index = 1) and video chunks (Data reference index = 1) are alternately and successively written on a disc. Each audio chunk is followed by each video chunk. In this example, on the audio track, values of which Flags = 4, track ID = 2, Data reference index = 1, Recorded data size = 1, and Repeat number = 1 are stored; on the video track, values of which Flags = 4, Track ID = 0, Data reference index = 0, Recorded data size = 1, and Repeat number = 1 are stored.

20 In this example, since the two tracks are interleaved and arranged, the values of the field "Flags" on both the tracks are 4 that represents an interleave format.

25 Since an audio chunk is followed by a video chunk corresponding thereto as a set, the values of Track ID = 2 and Data reference index = 1 of the video

track are assigned to the field "Track ID" and the field "Data reference index" of the audio track, respectively, so as to represent the dependant relation of a video chunk connected to an audio chunk.

5 In contrast, a value 0 that represents that no chunk is connected is assigned to the field "Track ID" and the field "Data reference index" of the video track so as to represent no chunk successively written.

10 As the number of chunks of audio data and video data that are successively written, a value 1 that represents one chunk is assigned to the field "Record data size" of the audio track and the video track. In addition, as the number of repeating times, a value 1 is assigned to the field "Repeat number" of the audio track and the video track.

15 Fig. 13B shows a second example. In the second example, there are one audio track (Track ID = 1) and one video track (Track ID = 2). Audio chunks (Data reference index = 1) and video chunks (Data
20 reference index = 1) are alternately and successively written on a disc. Each audio chunk is followed by each video chunk. In this example, on the audio track, values of which Flags = 4, track ID = 2, Data reference index = 0, Recorded data size = 1, and Repeat number =
25 1 are stored; on the video track, values of which Flags = 4, Track ID = 1, Data reference index = 1, Recorded data size = 1, and Repeat number =1 are stored.

Fig. 13C shows a third example. In the third example, there are one audio track (Track ID = 1) and one video track (Track ID = 2). Audio chunks (Data reference index = 1) and video chunks (Data reference index = 1) are alternately and successively written on a disc in such a manner that two audio chunks are followed by one video chunk. In this example, on the audio track, values of which Flags = 4, track ID = 2, Data reference index = 1, Recorded data size = 2, and Repeat number = 1 are stored; on the video track, values of which Flags = 4, Track ID = 0, Data reference index = 0, Recorded data size = 1, and Repeat number = 1 are stored.

Fig. 13D shows a fourth example. In the fourth example, there are one audio track (Track ID = 1) and one video track (Track ID = 2). Audio chunks (Data reference index = 1) and video chunks (Data reference index = 1) are alternately and successively written on a disc in such a manner that three sets of one audio chunk and one video chunk are successively written as one unit. In this example, on the audio track, values of which Flags = 4, track ID = 2, Data reference index = 1, Recorded data size = 1, and Repeat number = 3 are stored; on the video track, values of which Flags = 4, Track ID = 0, Data reference index = 0, Recorded data size = 1, and Repeat number = 3 are stored.

Fig. 13E shows a fifth example. In the fifth example, there are one audio track (Track ID = 1) and one video track (Track ID = 2). Audio chunks (Data reference index = 1) and video chunks (Data reference index = 1) are alternately and successively written on a disc in such a manner that two sets of two audio chunks and one video chunk are successively written as one unit. In this example, on the audio track, values of which Flags = 4, track ID = 2, Data reference index = 1, Recorded data size = 2, and Repeat number = 2 are stored; on the video track, values of which Flags = 4, Track ID = 0, Data reference index = 0, Recorded data size = 1, and Repeat number = 2 are stored.

Fig. 13F shows a sixth example. In the sixth example, there is only one audio track (Track ID = 1). Audio chunks (Data reference index = 1) are successively written on a disc. In this example, on the audio track, values of which Flags = 0, track ID = 0, Data reference index = 0, Recorded data size = 1, and Repeat number = 1 are stored.

Fig. 13G shows a seventh example. In the seventh example, there is only one audio track (Track ID = 1). Audio chunks (Data reference index = 1) are successively written on a disc in such a manner that three audio chunks are successively written as a unit. In this example, on the audio track, values of which Flags = 0, track ID = 0, Data reference index = 0,

Recorded data size = 3, and Repeat number = 1 are stored.

In the above description, the present invention is applied to a disc recording and reproducing apparatus having a built-in camera. However, it should be noted that the present invention can be applied to other apparatuses.

In addition, according to the present invention, part or all the hardware structure shown in Fig. 1 may be accomplished by software. Moreover, the software is stored in a record medium that can be read by a computer. An example of such a record medium is a CD-ROM.

In the above-mentioned embodiment, QuickTime was described. In addition, the present invention can be applied to computer software that allows a sequence of data that varies in a plurality of time sequences to be synchronously reproduced without need to use dedicated hardware.

According to the present invention, when data having a file structure is recorded to an optical disc, since the successive record length is matched with a plurality of second data units (for example, chunks of QuickTime), the accessibility and editing efficiency can be improved. In addition, according to the present invention, since information that represents the relation of a track on which chunks are successively

recorded and information that represents the number of
chunks or sets included in the successive record length
are recorded in a managing portion, a track on which
chunks are successively recorded can be easily
5 obtained.

Although the present invention has been shown
and described with respect to a best mode embodiment
thereof, it should be understood by those skilled in
the art that the foregoing and various other changes,
10 omissions, and additions in the form and detail thereof
may be made therein without departing from the spirit
and scope of the present invention.

What is claimed is:

1. A recording apparatus for recording video data to a rewritable optical disc, comprising:

encoding means for encoding video data
5 corresponding to a compression-encoding process;

converting means for converting the data
structure of the encoded video data received from said
encoding means into a file structure that allows a
moving picture to be synchronously reproduced by
10 computer software without need to use specially
dedicated hardware; and

recording means for recording data having the
file structure to an optical disc,

wherein the file structure has a first data
unit and a second data unit, the second data unit being
15 a set of the first data units, and

wherein a plurality of the second data units
is matched with a successive record length of which
data is written to the optical disc.

20 2. A recording apparatus for recording audio
data to a rewritable optical disc, comprising:

converting means for converting the data
structure of audio data or encoded audio data into a
file structure that allows a moving picture to be
25 synchronously reproduced by computer software without
need to use specially dedicated hardware; and

recording means for recording data having the

file structure to an optical disc,

wherein the file structure has a first data unit and a second data unit, the second data unit being a set of the first data units, and

5 wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

3. A recording apparatus for recording video data and audio data to a rewritable optical disc, comprising:

10 video encoding means for encoding video data corresponding to a compression-encoding process in a combination of an inter-frame predictive encoding process and a motion compensating process that allow a plurality of frames are structured as a group;

15 audio output means for outputting audio data that has been compression-encoded or non-compressed;

20 multiplexing means for converting the data structure of the encoded video data received from said encoding means and the data structure of the audio data received from said audio output means into respective file structures that allow a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware and
25 multiplexing the encoded video data and the audio data; and

recording means for recording the multiplexed

data to an optical disc,

wherein each of the file structures has a first data unit and a second data unit, the second data unit being a set of the first data units, and

5 wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

4. The recording apparatus as set forth in claim 3,

10 wherein in the multiplexed data, the duration of the encoded video data of the second data unit is almost equal to the duration of the audio data of the second data unit.

5. The recording apparatus as set forth in claim 3,

15 wherein in the multiplexed data, the encoded video data of the second data unit and audio data of the second data unit are alternately arranged, and

20 wherein a plurality of sets of the encoded video data of the second data unit and the audio data of the second data unit are matched with the successive record length.

6. The recording apparatus as set forth in claim 2 or 3,

25 wherein the audio data is compression-encoded corresponding to ATRAC, and

wherein the first data unit of the file

structure contains one or a plurality of sound units.

7. The recording apparatus as set forth in claim 1 or 2,

wherein the file structure further includes a data portion that describes management information, and wherein the data portion describes the number of the second data units contained in the successive record length.

8. The recording apparatus as set forth in claim 3,

wherein the file structure further includes a data portion that describes management information, and wherein the data portion describes a flag and the number of sets contained in the successive record length, the flag representing whether or not sets of encoded video data and audio data of the second data unit have been recorded in the data portion.

9. A recording method for recording video data to a rewritable optical disc, comprising the steps of:

encoding video data corresponding to a compression-encoding process;

converting the data structure of the encoded video data received at the encoding step into a file structure that allows a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware; and

recording data having the file structure to

an optical disc,

wherein the file structure has a first data unit and a second data unit, the second data unit being a set of the first data units, and

5 wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

10. A recording method for recording audio data to a rewritable optical disc, comprising the steps of:

10 converting the data structure of audio data or encoded audio data into a file structure that allows a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware; and

15 recording data having the file structure to an optical disc,

wherein the file structure has a first data unit and a second data unit, the second data unit being a set of the first data units, and

20 wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

11. A recording method for recording video data and audio data to a rewritable optical disc, comprising the steps of:

25 encoding video data corresponding to a compression-encoding process in a combination of an

inter-frame predictive encoding process and a motion compensating process that allow a plurality of frames are structured as a group;

outputting audio data that has been
5 compression-encoded or non-compressed;

converting the data structure of the encoded video data received at the encoding step and the data structure of the audio data received at the outputting step into respective file structures that allow a
10 moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware and multiplexing the encoded video data and the audio data; and

recording the multiplexed data to an optical
15 disc,

wherein each of the file structures has a first data unit and a second data unit, the second data unit being a set of the first data units, and

wherein a plurality of the second data units
20 is matched with a successive record length of which data is written to the optical disc.

12. A record medium on which a program for recording video data to a record medium has been recorded, the program causing a computer to perform the
25 steps of:

encoding video data corresponding to a compression-encoding process;

converting the data structure of the encoded
video data received at the encoding step into a file
structure that allows a moving picture to be
synchronously reproduced by computer software without
5 need to use specially dedicated hardware; and

recording data having the file structure to
an optical disc,

wherein the file structure has a first data
unit and a second data unit, the second data unit being
10 a set of the first data units, and

wherein a plurality of the second data units
is matched with a successive record length of which
data is written to the optical disc.

13. A record medium on which a program for
recording audio data to a record medium has been
15 recorded, the program causing a computer to perform the
steps of:

converting the data structure of audio data
or encoded audio data into a file structure that allows
20 a moving picture to be synchronously reproduced by
computer software without need to use specially
dedicated hardware; and

recording data having the file structure to
an optical disc,

25 wherein the file structure has a first data
unit and a second data unit, the second data unit being
a set of the first data units, and

wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

14. A record medium on which a program for recording video data and audio data to a record medium has been recorded, the program causing a computer to perform the steps of:

encoding video data corresponding to a compression-encoding process in a combination of an inter-frame predictive encoding process and a motion compensating process that allow a plurality of frames are structured as a group;

outputting audio data that has been compression-encoded or non-compressed;

converting the data structure of the encoded video data received at the encoding step and the data structure of the audio data received at the outputting step into respective file structures that allow a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware and multiplexing the encoded video data and the audio data; and

recording the multiplexed data to an optical disc,

wherein each of the file structures has a first data unit and a second data unit, the second data unit being a set of the first data units, and

wherein a plurality of the second data units
is matched with a successive record length of which
data is written to the optical disc.

ABSTRACT OF THE DISCLOSURE

A recording apparatus for recording video data to a rewritable optical disc is disclosed, that comprises an encoding means for encoding video data corresponding to a compression-encoding process, a converting means for converting the data structure of the encoded video data received from the encoding means into a file structure that allows a moving picture to be synchronously reproduced by computer software without need to use specially dedicated hardware, and a recording means for recording data having the file structure to an optical disc, wherein the file structure has a first data unit and a second data unit, the second data unit being a set of the first data units, and wherein a plurality of the second data units is matched with a successive record length of which data is written to the optical disc.

Fig. 1




Fig. 2




Fig. 3

one track video movie atom




Fig. 4




Fig. 5A




Fig. 5B




Fig. 6A

MPEG Audio
Elementary
Stream





Fig. 6B

Quick Time






Fig. 7A

Fig. 7B

Fig. 8A




Fig. 8B




Fig. 8C




Fig. 8D




Fig. 9D




Fig. 9C




Fig. 9B




Fig. 9A




Fig. 10

Fig. 12

```

Sample description atom {
  Atom size
  Type
  Version
  Flags
  Number of entries
  Sample description table {
    Sample description size
    Data format = 'DMPG' ← FORMAT TYPE IS
                          NEWLY DEFINED
    Reserved
    Data reference index
    Video sample description or Sound Sample description {
      Version
      Revision level
      Vendor
      ...
      [Extension size]      (4 byte)
      [Extension type]='stde' (4 byte)
      [Flags]               (1 byte)
      [Track ID]            (4 byte)
      [Data reference index] (2 byte)
      [Recorded data size]  (2 byte)
      [Repeat number]       (1 byte)
    }
  }
}

```

↑
FIELDS ARE
ADDITIONALLY
DEFINED
↓




Fig. 13A




Fig. 13B




Fig. 13C




Fig. 13D




Fig. 13E




Fig. 13F




Fig. 13G

FROMMER LAWRENCE & HAUG LLP

Page 1 of 1